

DATE: 2013-8-20 (YY/MM/DD)

Customer :

APPROVAL SHEET

PRODUCT: AC ADAPTOR(RoHS Compliant)

MODEL: APL315-0916

PART NO. ST-0121


V : A1

Receiver's stamp or signature

PLEASE APPROVE & RETURN BEFORE 2013-9-3
OR WE WOULD REGARD IT BEEN CONFIRMED.

RESPONSIBLE	APPROVED	ISSUED
		nishuang

ISSUES STAMP



Revised History

NO.	Revised Date	Description	Approved	Issued



Anthin Power Supply Co.,Ltd. (China)

TEL:+86-755-8980-7888

FAX:+86-755-8980-1111

<http://www.Anthin.cn>

info@anthin.cn

Anthin Japan Co.,Ltd. (Japan)

TEL:+81-45-730-5250

FAX:+81-45-730-5251

<http://www.Anthin.co.jp>

info@anthin.co.jp

Anthin	DESCRIPTION	SWITCHING POWER AC ADAPTER	SHEET NO.	1 OF 4
			VER:	A1
	MODEL NO.	APL315-0916	PART NO.	ST-0121
1.INPUT REQUIREMENT 2.OUTPUT SPECIFICATION 3.MECHANICAL 4.RELIABILITY 5.ENVIRONMENT 6.OUTLOOKING 7.SAFETY 8.QC CHECK 9.DIMENSION 10.LABEL 11.PACKING				

Anthin	DESCRIPTION	SWITCHING POWER AC ADAPTER	SHEET NO.	2 OF 4
			VER:	A1
	MODEL NO.	APL315-0916	PART NO.	ST-0121


1.INPUT REQUIREMENT

ITEM	SPECIFICATION	MIN	TYP.	MAX
NORMAL AC INPUT VOLTAGE	SINGLE PHASE	100Vac	110Vac/220Vac	240Vac
AC INPUT VOLTAGE RANGE	SINGLE PHASE	90Vac	110Vac/220Vac	264Vac
AC INPUT FREQUENCY	SINGLE PHASE	47Hz	50/60Hz	63Hz
AC INPUT CURRENT	TYPICAL INPUT VOLTAGE& OUTPUT AT FULL LOAD.			300mA
AC INRUSH CURRENT	TYPICAL INPUT VOLTAGE& OUTPUT AT FULL LOAD , 25℃.			30A
EFFICIENCY	TYPICAL INPUT VOLTAGE& OUTPUT AT FULL LOAD	65%		

2.OUTPUT SPECIFICATION

ITEM	SPECIFICATION	MIN	TYP.	MAX
NORMAL DC OUTPUT VOLTAGE			9Vdc	
DC OUTPUT VOLTAGE RANGE	TYPICAL OUTPUT VOLTAGE $\pm 5\%$	8.55V		9.45V
LOAD CURRENT RANGE		0A		1.6A
PEAK LOAD CURRENT	TIME<60S			2A
RIPPLE	TYPICAL INPUT VOLTAGE , TYPICAL LOAD CURRENT , 25℃			100mV
HOLD-UP TIME	AT TYPICAL INPUT VOLTAGE AND FULL LOAD	10mS		
TURN-ON DELAY	TYPICAL INPUT VOLTAGE AND TYPICAL LOAD			1S
OVER CURRENT PROTECTION	AUTO RECOVERY			
SHORT CIRCUIT PROTECTRON	THE ADAPTER SHALL NOT DAMAGE BY SHORT THE DC OUTPUT TO GROUND			
OVER VOLTAGE PROTECTION			10.4V	13.5V

*TEST MEASURES



C1: 0.1uF CERAMICS CAPACITOR
C2: 10uF 50V ALUMINUM CAPACITOR

Anthin	DESCRIPTION	SWITCHING POWER AC ADAPTER	SHEET NO.	3 OF 4
			VER:	A1
	MODEL NO.	APL315-0916	PART NO.	ST-0121

3.MECHANICAL

ITEM	SPECIFICATION OR TEST CONDITION	ACCEPTANCE CRITERIA
BENDING TEST	NORMAL TEMPERATURE THE CORD SHALL WITHSTAND WEIGHT OF 200g, SWINGING FROM LEFT TO RIGHT AT AN ANGLE OF 60 DEG. 1000CYCLE TIMES MIN. S/R SHALL WITHSTAND WEIGHT OF 1N. SWINGING FROM LEFT TO RIGHT AT AN ANGLE OF 60DEG. 1000CYCLE TIMES MIN. BENDING SPEED 40CYCLE/MINUTE	NO SHORT CIRCUIT NO BREAKAGE OF THE CORD
VIBRATION	FREQUENCY RANGE:10~55Hz AMPLITUDE:1.5mm ACCELERATION: 1G SWEEP 1 MINUTE FOR X,Y,Z,AXIS EACH	THERE SHALL BENO ABNORMALITY ON THE APPEARANCE STRUCTURE AND OPERATING

4.RELIABILITY

ITEM	TEST CONDITION	ACCEPTANCE CRITERIA
TEMPERATURE UP WITH TYPICAL LOAD	TEST THE SURFACE OF THE CASE WITH TYPICAL LOAD OUTPUT AND TYPICAL AC INPUT 50/60Hz	TEMPERATURE UP UNDER 35 DEGREES
HI-POT TEST	INPUT TO OUTPUT GRADUALLY RAISED FROM 0 TO THE 3000Vac AND HELD AT THAT VALUE FOR 3S,5mA	NO DAMAGE
INSULATION RESISTANCE	INPUT TO OUTPUT,DC 500V	>100MΩ
MTBF	TYPICAL INPUT&FULL LOAD , 25℃	50000 HOURS
LIFE	TYPICAL INPUT&FULL LOAD, 40℃ TYPICAL INPUT&FULL LOAD, 25℃	1YEARS ABOVE 2YEARS ABOVE
BURN-IN	AT 30℃(±10℃),NORMAL INPUT VOLTAGE	2~4 HOURS

5.ENVIRONMENT

ITEM	SPECIFICATION OR TEST CONDITION	min.	typ.	max.
OPERATING TEMPERATURE		0℃		40℃
STORAGE TEMPERATURE		-20℃		85℃
OPERATING HUMIDITY	NON-CONDENSING	5%RH		90%RH
STORAGE HUMIDITY	NON-CONDENSING	5%RH		90%RH

DESCRIPTION	SWITCHING POWER	SHEET NO.	4 OF 4
	AC ADAPTER	VER:	A1
	MODEL NO.	PART NO.	ST-0121

6.OUTLOOKING

DIMENSION

:76(L)X44(W)X26(H)mm

WEIGHT

:ABOUT 100g

AC INPUT TYPE

:2PIN INLE

DC OUTPUT TYPE

:5.5×2.1×9.5 S TYPE

DC OUTPUT CABLE

:USE 2468 20AWG WIRE

RoHS COMPLIANT

INDICATION

:LABEL

RoHS COMPLIANT

CASE MATERIAL

:94V-0 ABS+PC **BLACK**

RoHS COMPLIANT

PCB MATERIAL

:94V-0

RoHS COMPLIANT

7.SAFETY

COMPLY SAFETY STANDARDS	STANDARD	FILE NO.

EMI
CE

8.QC CHECK

ALL OF THE QUANTITY SHALL BE CHECKED BEFORE SHIPMENT,CHECK ITEM AS BELOW:


(1)DC PLUG POLE CHECK

(2)OCP FUNCTION CHECK

(3)DC OUTPUT VOLTAGE CHECK

(4)HIPOT&INSULATION CHECK

(5)OUTLOOKING CHECK



XXXX-XXXXXRoHS

RoHS COMPLIANT

流水号 (Number)


月 (Month)

年 (Year)

NOTE:

- 1.SILVER WORD(银字) ON BLACK BASE(黑底).
- 2.MATERIAL:PVC + MYLAR FILM
- 3.ROHS COMPLIANT.


TOLERANCE					FINISH				NAME: LABEL	
L ≤ 4	0.05	0.08	0.1	0.2					REV.	A1
4 < L ≤ 20	0.08	0.1	0.2	0.3						
20 < L ≤ 50	0.1	0.15	0.3	0.4						
50 < L ≤ 200	0.15	0.25	0.4	0.6						
200 < L	0.2	0.4	0.5	0.8	MATERIAL	QTY			PART NO.	ST-0121
DEG.		CHKD.	APPD.			UNIT	mm			
Anni				SCALE	REF.					
				REM.						






气泡袋:120*90

注:气泡袋不用胶纸固定

成品1PCS装入气泡袋+可换头放入小白盒
小白盒材质 (450G)
外径尺寸:长*宽*高
L*W*H (126*58*70mm)
TOLERANCE: ± 1



WHITE INNER BOX+OUT CARTON
WHITE INNER BOX OUT SIDE DIMENSION :
L*W*H (126*58*70mm)
TOLERANCE: ± 1



每层装26个小白盒，共可装3层。

成品78PCS装入外箱
外箱3段: K=A
外径尺寸:长*宽*高
L555*W380*H236mm
平卡尺寸:长*宽
L535*W368mm

TOLERANCE					FINISH							
L<4	4<L<20	20<L<50	50<L<200	200<L								
±0.05	±0.08	±0.1	±0.2	±0.3	MATERIAL		REV.	A1	NAME	12.PACKING		
±0.08	±0.1	±0.2	±0.3	±0.4								
±0.1	±0.15	±0.3	±0.4	±0.5								
±0.15	±0.25	±0.4	±0.5	±0.6								
DEG.	CHKD.	APPD.		UNIT	mm			PART NO.	ST-0121			
Anni			SCALE	REF.								
				DWG NO.								