

DATE: 2013-8-20 (YY/MM/DD)

Customer :

## APPROVAL SHEET

PRODUCT: AC ADAPTOR(RoHS Compliant)

MODEL: APK315-0325

PART NO. ST-0141


V : A1

Receiver's stamp or signature

PLEASE APPROVE & RETURN BEFORE 2013-9-3  
OR WE WOULD REGARD IT BEEN CONFIRMED.

| RESPONSIBLE | APPROVED | ISSUED   |
|-------------|----------|----------|
|             |          | nishuang |

ISSUES STAMP



### Revised History

| NO. | Revised Date | Description | Approved | Issued |
|-----|--------------|-------------|----------|--------|
|     |              |             |          |        |
|     |              |             |          |        |
|     |              |             |          |        |
|     |              |             |          |        |



Anthin Power Supply Co.,Ltd. (China)

TEL:+86-755-8980-7888

FAX:+86-755-8980-1111

<http://www.Anthin.cn>

[info@anthin.cn](mailto:info@anthin.cn)

Anthin Japan Co.,Ltd. (Japan)

TEL:+81-45-730-5250

FAX:+81-45-730-5251

<http://www.Anthin.co.jp>

[info@anthin.co.jp](mailto:info@anthin.co.jp)

|                                                                                                                                                                                                                                                                               |                    |                                       |                  |                |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------|---------------------------------------|------------------|----------------|
| <b>Anthin</b>                                                                                                                                                                                                                                                                 | <b>DESCRIPTION</b> | <b>SWITCHING POWER<br/>AC ADAPTER</b> | <b>SHEET NO.</b> | <b>1 OF 4</b>  |
|                                                                                                                                                                                                                                                                               |                    |                                       | <b>VER:</b>      | <b>A1</b>      |
|                                                                                                                                                                                                                                                                               | <b>MODEL NO.</b>   | <b>APK315-0325</b>                    | <b>PART NO.</b>  | <b>ST-0141</b> |
| <div>1.INPUT REQUIREMENT</div> <div>2.OUTPUT SPECIFICATION</div> <div>3.MECHANICAL</div> <div>4.RELIABILITY</div> <div>5.ENVIRONMENT</div> <div>6.OUTLOOKING</div> <div>7.SAFETY</div> <div>8.QC CHECK</div> <div>9.DIMENSION</div> <div>10.LABEL</div> <div>11.PACKING</div> |                    |                                       |                  |                |

|               |                    |                                       |                  |                |
|---------------|--------------------|---------------------------------------|------------------|----------------|
| <b>Anthin</b> | <b>DESCRIPTION</b> | <b>SWITCHING POWER<br/>AC ADAPTER</b> | <b>SHEET NO.</b> | <b>2 OF 4</b>  |
|               |                    |                                       | <b>VER:</b>      | <b>A1</b>      |
|               | <b>MODEL NO.</b>   | <b>APK315-0325</b>                    | <b>PART NO.</b>  | <b>ST-0141</b> |

## 1.INPUT REQUIREMENT

| ITEM                    | SPECIFICATION                                     | MIN    | TYP.          | MAX    |
|-------------------------|---------------------------------------------------|--------|---------------|--------|
| NORMAL AC INPUT VOLTAGE | SINGLE PHASE                                      | 100Vac | 110Vac/220Vac | 240Vac |
| AC INPUT VOLTAGE RANGE  | SINGLE PHASE                                      | 90Vac  | 110Vac/220Vac | 264Vac |
| AC INPUT FREQUENCY      | SINGLE PHASE                                      | 47Hz   | 50/60Hz       | 63Hz   |
| AC INPUT CURRENT        | TYPICAL INPUT VOLTAGE& OUTPUT AT FULL LOAD.       |        |               | 300mA  |
| AC INRUSH CURRENT       | TYPICAL INPUT VOLTAGE& OUTPUT AT FULL LOAD , 25℃. |        |               | 30A    |
| EFFICIENCY              | TYPICAL INPUT VOLTAGE& OUTPUT AT FULL LOAD        | 65%    |               |        |

## 2.OUTPUT SPECIFICATION

| ITEM                     | SPECIFICATION                                                 | MIN   | TYP. | MAX   |
|--------------------------|---------------------------------------------------------------|-------|------|-------|
| NORMAL DC OUTPUT VOLTAGE |                                                               |       | 3Vdc |       |
| DC OUTPUT VOLTAGE RANGE  | TYPICAL OUTPUT VOLTAGE ±5%                                    | 2.85V |      | 3.15V |
| LOAD CURRENT RANGE       |                                                               | 0A    |      | 2.5A  |
| PEAK LOAD CURRENT        | TIME<60S                                                      |       |      | 3A    |
| RIPPLE                   | TYPICAL INPUT VOLTAGE , TYPICAL LOAD CURRENT , 25℃            |       |      | 50mV  |
| HOLD-UP TIME             | AT TYPICAL INPUT VOLTAGE AND FULL LOAD                        | 10mS  |      |       |
| TURN-ON DELAY            | TYPICAL INPUT VOLTAGE AND TUP LOAD CURRENT                    |       |      | 1S    |
| OVER CURRENT PROTECTION  | AUTO RECOVERY                                                 |       |      |       |
| SHORT CIRCUIT PROTECTRON | THE ADAPTER SHALL NOT DAMAGE BY SHORT THE DC OUTPUT TO GROUND |       |      |       |
| OVER VOLTAGE PROTECTION  |                                                               |       | 3.5V | 4.5V  |

## \*TEST MEASURES



C1: 0.1uF CERAMICS CAPACITOR  
C2: 10uF 50V ALUMINUM CAPACITOR

|        |             |                               |           |         |
|--------|-------------|-------------------------------|-----------|---------|
| Anthin | DESCRIPTION | SWITCHING POWER<br>AC ADAPTER | SHEET NO. | 3 OF 4  |
|        |             |                               | VER:      | A1      |
|        | MODEL NO.   | APK315-0325                   | PART NO.  | ST-0141 |

### 3.MECHANICAL

| ITEM         | SPECIFICATION OR TEST CONDITION                                                                                                                                                                                                                                                    | ACCEPTANCE CRITERIA                                                             |
|--------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------|
| BENDING TEST | NORMAL TEMPERATURE<br>THE CORD SHALL WITHSTAND WEIGHT OF 200g, SWINGING FROM LEFT TO RIGHT AT AN ANGLE OF 60 DEG. 1000CYCLE TIMES MIN.<br>S/R SHALL WITHSTAND WEIGHT OF 1N. SWINGING FROM LEFT TO RIGHT AT AN ANGLE OF 60DEG. 1000CYCLE TIMES MIN.<br>BENDING SPEED 40CYCLE/MINUTE | NO SHORT CIRCUIT<br>NO BREAKAGE OF THE CORD                                     |
| VIBRATION    | FREQUENCY RANGE:10~55Hz<br>AMPLITUDE:1.5mm<br>ACCELERATION: 1G<br>SWEEP 1 MINUTE FOR X,Y,Z,AXIS EACH                                                                                                                                                                               | THERE SHALL BENO<br>ABNORMALITY ON THE<br>APPEARANCE STRUCTURE<br>AND OPERATING |

### 4.RELIABILITY

| ITEM                                | TEST CONDITION                                                                                 | ACCEPTANCE CRITERIA                |
|-------------------------------------|------------------------------------------------------------------------------------------------|------------------------------------|
| TEMPERATURE UP WITH<br>TYPICAL LOAD | TEST THE SURFACE OF THE CASE WITH TYPICAL<br>LOAD OUTPUT AND TYPICAL AC INPUT 50/60Hz          | TEMPERATURE UP UNDER<br>35 DEGREES |
| HI-POT TEST                         | INPUT TO OUTPUT<br>GRADUALLY RAISED FROM 0 TO THE 3000Vac AND HELD<br>AT THAT VALUE FOR 3S,5mA | NO DAMAGE                          |
| INSULATION RESISTANCE               | INPUT TO OUTPUT,DC 500V                                                                        | >100MΩ                             |
| MTBF                                | TYPICAL INPUT&FULL LOAD , 25℃                                                                  | 50000 HOURS                        |
| LIFE                                | TYPICAL INPUT&FULL LOAD, 40℃<br>TYPICAL INPUT&FULL LOAD, 25℃                                   | 1YEARS ABOVE<br>2YEARS ABOVE       |
| BURN-IN                             | AT 30℃(±10℃),NORMAL INPUT VOLTAGE                                                              | 2~4 HOURS                          |

### 5.ENVIRONMENT

| ITEM                  | SPECIFICATION OR TEST CONDITION | min. | typ. | max.  |
|-----------------------|---------------------------------|------|------|-------|
| OPERATING TEMPERATURE |                                 | 0℃   |      | 40℃   |
| STORAGE TEMPERATURE   |                                 | -20℃ |      | 85℃   |
| OPERATING HUMIDITY    | NON-CONDENSING                  | 5%RH |      | 90%RH |
| STORAGE HUMIDITY      | NON-CONDENSING                  | 5%RH |      | 90%RH |

|        |             |                 |           |         |
|--------|-------------|-----------------|-----------|---------|
| Anthin | DESCRIPTION | SWITCHING POWER | SHEET NO. | 4 OF 4  |
|        |             | AC ADAPTER      | VER:      | A1      |
|        | MODEL NO.   | APK315-0325     | PART NO.  | ST-0141 |

6.OUTLOOKING

DIMENSION

WEIGHT

AC INPUT TYPE

DC OUTPUT TYPE

:70(L)X45(W)X30.5(H)mm

:ABOUT 130g

:WALL MOUNT

: 5.5×2.1×9.5 S TYPE



DC OUTPUT CABLE

INDICATION

CASE MATERIAL

PCB MATERIAL

:USE UL SPT-1 18AWG WIRE

:LABEL

:94V-0 ABS+PC BLACK

:94V-0

RoHS COMPLIANT

RoHS COMPLIANT

RoHS COMPLIANT

RoHS COMPLIANT

7.SAFETY

|                         |          |          |
|-------------------------|----------|----------|
| COMPLY SAFETY STANDARDS | STANDARD | FILE NO. |
|                         |          |          |
|                         |          |          |
|                         |          |          |

EMI

CE

8.QC CHECK

ALL OF THE QUANTITY SHALL BE CHECKED BEFORE SHIPMENT,CHECK ITEM AS BELOW:

(1)DC PLUG POLE CHECK


(2)OCP FUNCTION CHECK

(3)DC OUTPUT VOLTAGE CHECK


(4)HIPOT&INSULATION CHECK

(5)OUTLOOKING CHECK






XXXX-XXXXXRoHS



# NOTE:



- 1.SILVER WORD(银字) ON BLACK BASE(黑底).
- 2.MATERIAL:PVC + MYLAR FILM
- 3.ROHS COMPLIANT.

| TOLERANCE    |      |       |     |       | FINISH                                                                              |       |      |  | NAME: |      | LABEL    |         |
|--------------|------|-------|-----|-------|-------------------------------------------------------------------------------------|-------|------|--|-------|------|----------|---------|
| 1 ≤ L        | 0.05 | 0.08  | 0.1 | 0.2   |                                                                                     |       |      |  | REV.  | A1   |          |         |
| 4 < L ≤ 20   | 0.08 | 0.1   | 0.2 | 0.3   | MATERIAL                                                                            | QTY   |      |  |       |      | PART NO. | ST-0141 |
| 20 < L ≤ 50  | 0.1  | 0.15  | 0.3 | 0.4   |                                                                                     |       |      |  |       |      |          |         |
| 50 < L ≤ 200 | 0.15 | 0.25  | 0.4 | 0.6   |                                                                                     |       |      |  |       |      |          |         |
| 200 < L      | 0.2  | 0.4   | 0.6 | 0.8   |                                                                                     |       |      |  |       |      |          |         |
| DEG.         |      | CHKD. |     | APPD. |  | UNIT  | mm   |  |       | REV. | A1       |         |
| Anni         |      |       |     |       |                                                                                     | SCALE | REF. |  |       |      |          |         |
|              |      |       |     |       |                                                                                     | REM.  |      |  |       |      |          |         |




成品1PCS装入小白盒  
小白盒材质 ( 450G )  
外径尺寸 : 长\*宽\*高  
L\*W\*H ( 83\*66\*55mm )  
TOLERANCE :  $\pm 1$

WHITE INNER BOX+OUT CARTON  
WHITE INNER BOX OUT SIDE DIMENSION :  
L\*W\*H ( 83\*66\*55mm )  
TOLERANCE :  $\pm 1$



每层装39个小白盒，共可装3层。



成品117PCS装入外箱  
外箱3段 : K=A  
外径尺寸 : 长\*宽\*高  
L555\*W380\*H236mm  
平卡尺寸 : 长\*宽  
L535\*W368mm

| TOLERANCE    |       |       |         |      | FINISH |    |          |         |
|--------------|-------|-------|---------|------|--------|----|----------|---------|
| L < 4        | ±0.05 | ±0.08 | ±0.1    | ±0.2 |        |    |          |         |
| 4 < L < 20   | ±0.08 | ±0.1  | ±0.2    | ±0.3 |        |    |          |         |
| 20 < L < 50  | ±0.1  | ±0.15 | ±0.3    | ±0.4 |        |    |          |         |
| 50 < L < 100 | ±0.15 | ±0.25 | ±0.4    | ±0.6 |        |    |          |         |
| 100 < L      | ±0.2  | ±0.4  | ±0.5    | ±0.8 |        |    |          |         |
| DEG.         | CHKD. | APPD. | UNIT    | mm   | REV.   | A1 | NAME     | PACKING |
| Anni         |       |       | SCALE   | REF. |        |    | PART NO. | ST-0141 |
|              |       |       | DWG NO. |      |        |    |          |         |