

DATE: 2013-8-21 (YY/MM/DD)

Customer :

APPROVAL SHEET

PRODUCT: AC ADAPTOR(RoHS Compliant)

MODEL: API365-1250

PART NO. ST-0256


V : A1

Receiver's stamp or signature

PLEASE APPROVE & RETURN BEFORE 2013-9-4
OR WE WOULD REGARD IT BEEN CONFIRMED.

RESPONSIBLE	APPROVED	ISSUED
		nishuang

ISSUES STAMP



Revised History

NO.	Revised Date	Description	Approved	Issued



Anthin Power Supply Co.,Ltd. (China)

TEL:+86-755-8980-7888

FAX:+86-755-8980-1111

<http://www.Anthin.cn>

info@anthin.cn

Anthin Japan Co.,Ltd. (Japan)

TEL:+81-45-730-5250

FAX:+81-45-730-5251

<http://www.Anthin.co.jp>

info@anthin.co.jp

Anthin	DESCRIPTION	SWITCHING POWER	SHEET NO.	1 OF 4
		AC ADAPTER	VER:	A1
	MODEL NO.	API365-1250	PART NO.	ST-0256
1.INPUT REQUIREMENT 2.OUTPUT SPECIFICATION 3.MECHANICAL 4.RELIABILITY 5.ENVIRONMENT 6.OUTLOOKING 7.SAFETY 8.QC CHECK 9.DIMENSION 10.LABEL 11.PACKING				

Anthin	DESCRIPTION	SWITCHING POWER AC ADAPTER	SHEET NO.	2 OF 4
			VER:	A1
	MODEL NO.	API365-1250	PART NO.	ST-0256


1.INPUT REQUIREMENT

ITEM	SPECIFICATION	MIN	TYP.	MAX
NORMAL AC INPUT VOLTAGE	SINGLE PHASE	100Vac	110Vac/220Vac	240Vac
AC INPUT VOLTAGE RANGE	SINGLE PHASE	90Vac	110Vac/220Vac	264Vac
AC INPUT FREQUENCY	SINGLE PHASE	47Hz	50/60Hz	63Hz
AC INPUT CURRENT	TYPICAL INPUT VOLTAGE& OUTPUT AT FULL LOAD.			1500mA
AC INRUSH CURRENT	TYPICAL INPUT VOLTAGE& OUTPUT AT FULL LOAD , 25℃.			30A
EFFICIENCY	TYPICAL INPUT VOLTAGE& OUTPUT AT FULL LOAD	65%		

2.OUTPUT SPECIFICATION

ITEM	SPECIFICATION	MIN	TYP.	MAX
NORMAL DC OUTPUT VOLTAGE			12Vdc	
DC OUTPUT VOLTAGE RANGE	TYPICAL OUTPUT VOLTAGE ±5%	11.4V		12.6V
LOAD CURRENT RANGE		0A		5A
PEAK LOAD CURRENT	TIME<60S			6.5A
RIPPLE	TYPICAL INPUT VOLTAGE , TYPICAL LOAD CURRENT , 25℃			120mV
HOLD-UP TIME	AT TYPICAL INPUT VOLTAGE AND FULL LOAD	10mS		
TURN-ON DELAY	TYPICAL INPUT VOLTAGE AND TYPICAL LOAD			2S
OVER CURRENT PROTECTION	AUTO RECOVERY			
SHORT CIRCUIT PROTECTRON	THE ADAPTER SHALL NOT DAMAGE BY SHORT THE DC OUTPUT TO GROUND			
OVER VOLTAGE PROTECTION			14.4V	18V

*TEST MEASURES



C1: 0.1uF CERAMICS CAPACITOR
C2: 10uF 50V ALUMINUM CAPACITOR

Anthin	DESCRIPTION	SWITCHING POWER AC ADAPTER	SHEET NO.	3 OF 4
			VER:	A1
	MODEL NO.	API365-1250	PART NO.	ST-0256

3.MECHANICAL

ITEM	SPECIFICATION OR TEST CONDITION	ACCEPTANCE CRITERIA
BENDING TEST	NORMAL TEMPERATURE THE CORD SHALL WITHSTAND WEIGHT OF 200g, SWINGING FROM LEFT TO RIGHT AT AN ANGLE OF 60 DEG. 1000CYCLE TIMES MIN. S/R SHALL WITHSTAND WEIGHT OF 1N. SWINGING FROM LEFT TO RIGHT AT AN ANGLE OF 60DEG. 1000CYCLE TIMES MIN. BENDING SPEED 40CYCLE/MINUTE	NO SHORT CIRCUIT NO BREAKAGE OF THE CORD
VIBRATION	FREQUENCY RANGE:10~55Hz AMPLITUDE:1.5mm ACCELERATION: 1G SWEEP 1 MINUTE FOR X,Y,Z,AXIS EACH	THERE SHALL BENO ABNORMALITY ON THE APPEARNCE STRUCTURE AND OPERATING

4.RELIABILITY

ITEM	TEST CONDITION	ACCEPTANCE CRITERIA
TEMPERATURE UP WITH TYPICAL LOAD	TEST THE SURFACE OF THE CASE WITH TYPICAL LOAD OUTPUT AND TYPICAL AC INPUT 50/60Hz	TEMPERATURE UP UNDER 35 DEGREES
HI-POT TEST	INPUT TO OUTPUT 3000Vac 3 SECONDS 5mA	NO DAMAGE
INSULATION RESISTANCE	INPUT TO OUTPUT,DC 500V	>100MΩ
MTBF	TYPICAL INPUT&FULL LOAD , 25℃	50000 HOURS
LIFE	TYPICAL INPUT&FULL LOAD, 40℃ TYPICAL INPUT&FULL LOAD, 25℃	1YEARS ABOVE 2YEARS ABOVE
BURN-IN	AT 30℃(±10℃),NORMAL INPUT VOLTAGE	2~4 HOURS

5.ENVIRONMENT

ITEM	SPECIFICATION OR TEST CONDITION	min.	typ.	max.
OPERATING TEMPERATURE		0℃		40℃
STORAGE TEMPERATURE		-20℃		85℃
OPERATING HUMILITY	NON-CONDENSING	5%RH		90%RH
STORAGE HUMILITY	NON-CONDENSING	5%RH		90%RH

Anthin	DESCRIPTION	SWITCHING POWER	SHEET NO.	4 OF 4
		AC ADAPTER	VER:	A1
	MODEL NO.	API365-1250	PART NO.	ST-0256

6.OUTLOOKING

DIMENSION

WEIGHT

AC INPUT TYPE

DC OUTPUT TYPE

:108(L)X48.2(W)X30.5(H)mm

:ABOUT 240g

:2PIN 日规八字尾 1.2米AC线

: 5.5×2.1×9.5mm S TYPE



DC OUTPUT CABLE

INDICATION

CASE MATERIAL

PCB MATERIAL

:USE UL SPT-1 18AWG WIRE

:LABEL

:94V-0 ABS+PC BLACK

:94V-0

ROHS COMPLIANT

ROHS COMPLIANT

ROHS COMPLIANT

ROHS COMPLIANT

7.SAFETY

COMPLY SAFETY STANDARDS	STANDARD	FILE NO.
PSE		

EMI

CE

8.QC CHECK

ALL OF THE QUANTITY SHALL BE CHECKED BEFORE SHIPMENT,CHECK ITEM AS BELOW:


(1)DC PLUG POLE CHECK

(2)OCP FUNCTION CHECK



(3)DC OUTPUT VOLTAGE CHECK

(4)HIPOT&INSULATION CHECK


(5)OUTLOOKING CHECK



TOLERANCE					FINISH		XXXXXX		NAME		DIMENSION
L&F	±0.05	±0.08	±0.1	±0.2	±0.3						
4-4.470	±0.08	±0.1	±0.2	±0.3	±0.4	MATERIAL		UNIT		REV.	A 1
20-4.450	±0.1	±0.15	±0.3	±0.4	±0.6						
50-4.200	±0.15	±0.25	±0.5	±0.6	±0.8						
200-L	±0.2	±0.4	±0.5	±0.8	±1.0						
DRG.	CIRCU.	APPR.					UNIT		mm		
jmh			SCALE				REV.		XXXX		PART NO.
							XXXX		XXXX		
											ST-0256



TOLERANCE										NAME: (PSE JET) AC CORD		
L & 4	±0.03	±0.08	±0.1	±0.2	FINISH	XXXXXX						
4 < L & 30	±0.05	±0.1	±0.15	±0.3	±0.4	MATERIAL	XXXXXX	QTY.	XXX			
30 < L & 50	±0.1	±0.15	±0.3	±0.4	±0.6							
50 < L & 200	±0.15	±0.25	±0.4	±0.6	±0.8							
200 < L	±0.2	±0.4	±0.5	±0.8								
DEG.	CHKD.	APPD.								UNIT	mm	REV
SCALE						REF.	XXXX	PART NO.	ST-0256			
						REM.	XXXX					



XXXX-XXXXXRoHS

RoHS COMPLIANT

流水号 (Number)


月 (Month)

年 (Year)

NOTE:




- 1.SILVER WORD(银字) ON BLACK BASE(黑底).
- 2.MATERIAL:PVC + MYLAR FILM
- 3.ROHS COMPLIANT.

TOLERANCE					FINISH				NAME:		LABEL
1 < L < 4	0.05	0.08	0.1	0.2					REV.	A1	
4 < L < 20	0.08	0.1	0.2	0.3	MATERIAL	QTY					PART NO.
20 < L < 50	0.1	0.15	0.3	0.4							
50 < L < 200	0.15	0.25	0.4	0.6							
200 < L	0.2	0.4	0.5	0.8							
DEG.		CHKD.		APPD.			UNIT	mm			
Anni							REF.				
							REM.				



成品1PCS+1条AC线装入小白盒
小白盒材质 (450G)
外径尺寸 : 长*宽*高
L*W*H (136*58*77mm)
TOLERANCE : ± 1

WHITE INNER BOX+OUT CARTON
WHITE INNER BOX OUT SIDE DIMENSION :
L*W*H (136*58*77mm)
TOLERANCE : ± 1



成品67PCS装入外箱
外箱3段 : K=A
外径尺寸 : 长*宽*高
L555*W380*H236mm
平卡尺寸 : 长*宽
L535*W368mm

TOLERANCE						FINISH				NAME	12.PACKING
L < 1	1 < L ≤ 20	20 < L ≤ 50	50 < L ≤ 100	100 < L			REV.	A1			
±0.05	±0.08	±0.1	±0.2	±0.3	MATERIAL				PART NO.	ST-0256	
±0.08	±0.1	±0.2	±0.3	±0.4							
±0.1	±0.15	±0.25	±0.4	±0.6							
±0.2	±0.4	±0.5	±0.8								
DEG.	CHKD.	APPD.		UNIT	mm				PART NO.	ST-0256	
Anni			SCALE	REF.							
				DWG NO.							